

VOLCLAY® CG-50

GRANULAR SODIUM BENTONITE

DESCRIPTION

VOLCLAY® CG-50 is a natural, granular, high-swelling Wyoming sodium bentonite recommended for slurry wall applications.

RECOMMENDED USE

VOLCLAY® CG-50 can be used to seal earthen structures, general sealing, and slurry wall construction.

COMPOSITION

Sodium bentonite is a hydrous silicate of alumina primarily consisting of the clay mineral montmorillonite, which swells several times its own volume when, wetted.

FREE SWELL

24 ml/2g minimum (ACC 1010).

MOISTURE CONTENT

12 percent maximum as shipped.

PARTICLE SIZING

5 percent max. retained on a #10 mesh (2.00 mm) sieve 15 percent max. passing a #200 mesh (75 mm) sieve (ASTM D422).

DRY BULK DENSITY

65 lbs/ft³ (1,040 kg/m³) typical.

FILTRATE LOSS

18 ml maximum (API 13A).

PACKAGING

50 lb (22.7 kg) bag, 48 per pallet, 1 ton or 2 ton supersacks, or bulk. All pallets are plastic-wrapped.



✉ | Unit 101 / 434 St. Kilda Rd. Melbourne, VIC 3004, Australia | T: +61 3 5272 8100
| www.cetco.com/dpg | enquiries.au@mineralstech.com

UPDATED: JULY 2016

© 2018 Minerals Technologies Inc. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please contact CETCO sales team. CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.

FORM: TDS_VOLCLAY_CG-50_AU_EN_201606_V1_1



CETCO®